



DESCRIPTION

This single axle multi-utility trailer from DK2 is one of the most versatile trailers on the market. Sitting on a solid square tube cambered axle with 12-inch, 6-ply bias tires and a load capacity of 1,639 pounds. When the front and back load-bearing gates are down, the trailer bed extends to nearly 12 feet in length, and the tilt/dump capability that makes it easy to load or unload heavy items. Fabricated from 100% steel, all of the components are reinforced, adjustable, removable and/or interchangeable.

SPECIFICATION

PAYLOAD CAPACITY	1,639 lb (743.4 kg)
GVWR	2,073 lb (940.3 kg)
WHEELS & TIRES	D.O.T. 5.30-12 6-ply bias tires with 5 x 4.5" (11.4 cm) bolt pattern
MATERIAL	Fully welded heavy-duty UV powder coated tubular steel
SIDE PANELS	Corrugated reinforced steel
DROP GATES	24" (61 cm) load-bearing corrugated reinforced steel
FLOORING	Corrugated reinforced steel panel
DUMP BED	2-position, axle-mounted with quick-release lock pin
LIGHTING	Pre-wired, quick-connect D.O.T LED
BED DIMENSIONS	88" (L) x 52" (W) 223.5 cm (L) x 132.1 cm (W)
FLOOR HEIGHT	20" (50.8 cm)
HITCH HEIGHT	16" (40.6 cm)
DIMENSIONS	177" (L) x 65" (W) x 36" (H) 449.6 cm (L) x 165.1 cm (W) x 91.4 cm (H)
WEIGHT	434.3 lb (197 kg)
SHIPPING DIMENSIONS	88" (L) x 55" (W) x 9" (H) 223.5 cm (L) x 139.7 cm (W) x 22.9 cm (H)
SHIPPING WEIGHT	458.6 lb (208 kg)
WARRANTY	1-year limited

4.5FT x 7.5FT SINGLE **AXLE MULTI-UTILITY** TRAILER

ITEM NUMBER

MMT5X7

39

UPC

826518003391

FEATURES

- Constructed with fully welded heavyduty UV powder-coated tubular steel
- Corrugated reinforced steel floor panel **1**
- Corrugated reinforced steel side panels 2
- 24" (61 cm) load-bearing corrugated steel drop gates, extending the length of the trailer to 11.3 ft (3.4 m) 3
- Solid square tube cambered axle
- 2-position axle-mounted dump bed with quick release lock pin 🕙
- D.O.T. 5.30-12 bias tires with 5 x 4.5" (11.4 cm) bolt pattern 5
- Heavy-duty tail light protectors
- Quick-connect D.O.T. LED lighting with side markers
- Ships in a single package
- 2" (5.08 cm) coupler on an A-frame tongue for added stability
- · Includes all necessary paperwork for registration



